



NOTES:

- A. SLOPE PROTECTION SHOWN IN THIS DETAIL INCLUDES MINIMUM REQUIREMENTS.
- B. SLOPE PROTECTION SHALL BE DESIGNED FOR SITE SPECIFIC CONDITIONS BY A DESIGN PROFESSIONAL REGISTERED IN THE STATE OF WASHINGTON.
- C. JUTE/COIR FABRIC MAY BE USED IN LIEU OF WALERS AND STAKING. JUTE FABRIC AND STAKES SHALL BE 100% BIODEGRADABLE MATERIAL WITH AN 18 MONTH LIFE AND SHALL BE SECURED IN PLACE ACCORDING TO MANUFACTURER'S RECOMMENDATIONS.
- D. STRAW WATTLES MAY BE USED IF APPROVED BY THE PARK PROJECT MANAGER. STRAW WATTLES SHALL BE INSTALLED IN ACCORDANCE WITH WSDOT STANDARD PLAN I-30.30-00 AND SHALL BE MADE OF 100% BIODEGRADABLE MATERIAL WITH AN 18 MONTH LIFE.
- E. WOOD STAKES AND WALERS SHALL BE ALL NATURAL WOOD SPECIES, UNTREATED.
- F. EXTENT AND LENGTH OF WALERS SHALL BE SHOWN ON THE FINAL GRADING PLAN.
- G. IF HARD SUBGRADES ARE ENCOUNTERED, WOOD STAKES MAY NEED TO BE MECHANICALLY DRIVEN INTO THE GROUND TO ACHIEVE THE REQUIRED EMBEDMENT DEPTH.

PARKS AND RECREATION
DESIGN AND DEVELOPMENT
JUNE 3, 2010

CITY OF BELLINGHAM
SLOPE PROTECTION
Scale: 1/2" = 1'-0"

DRAWING
2270.01